



DITCH ENCLOSURE DETAIL

CITY OF
MUNROE FALLS

NOTES:

- DITCH ENCLOSURE MAY ONLY BE PERFORMED WHERE APPROVED BY THE CITY. NOT ALL DITCHES MAY BE ENCLOSED.
- ALL ENCLOSURES SHALL ENSURE THAT POSITIVE DRAINAGE IS PROVIDED.
- MINIMUM PIPE DIAMETER USED SHALL BE 12" UNLESS THE CITY DETERMINES A LARGER SIZE IS REQUIRED.
- BACKFILL USED SHALL BE NO. 8 OR NO. 57 MATERIAL OR APPROVED EQUAL.
- BACKFILL SHALL BE PROPERLY COMPACTED BY METHODS APPROVED BY THE CITY.
- THE PROPERTY OWNER OR AUTHORIZED REPRESENTATIVE SHALL SUBMIT, IN WRITING, THE PROPOSED MATERIAL AND INSTALLATION METHODS FOR APPROVAL PRIOR TO BEGINNING WORK.
- WORK PERFORMED PRIOR TO CITY APPROVAL OR WITHOUT THE PRESENCE OF A CITY APPOINTED INSPECTOR IS PROHIBITED AND WILL RESULT IN THE REMOVAL OF SAID WORK.
- CATCH BASINS SHALL BE INSTALLED AT ALL LOW POINTS, WHERE DEEMED NECESSARY BY THE CITY, AND WHERE THE NEW DITCH ENCLOSURE TIES INTO EXISTING DRIVE PIPES.
- LONG ENCLOSURES WILL REQUIRE THE INSTALLATION OF CATCH BASINS NO FURTHER THAN 300' APART.
- ALL CONDUIT, CATCH BASINS, AND OTHER MATERIAL INSTALLED WITH THE PROPOSED DITCH ENCLOSURE SHALL FALL UNDER THE RESPONSIBILITY OF THE HOMEOWNER TO MAINTAIN AND/OR REPAIR.
- THE CITY RESERVES THE RIGHT TO PERFORM MAINTENANCE AND/OR REPAIR OF THE ENCLOSURE WHEN DEEMED NECESSARY.
- CATCH BASIN STRUCTURES SHALL BE INSTALLED PER ODOT ITEM 611.

O:\2021\2021037\00 General Engineering Services\Ditch Enclosure Detail.dwg